


BOUNDARY LINE ADJUSTMENT
 A PORTION OF
 SE1/4 NW1/4, SW1/4 NW1/4, NW1/4 SW1/4, NE1/4 SW1/4,
 SW1/4 SW1/4, SE1/4 SW1/4, SE1/4 NE1/4, SW1/4 NE1/4,
 NW1/4 SE1/4, NE1/4 SE1/4, SE1/4 SE1/4, SW1/4 SE1/4,
 SEC. 7 - T.19N. - R.15E., W.M.
 KITTITAS COUNTY, WASHINGTON



LEGEND

- ▲ = ANGLE POINT
- = PREVIOUSLY SET 1/2" x 24" REBAR W/PLASTIC CAP: K. BLUHM LS 29269 ON REFERENCE SURVEY #3
- = FOUND 5/8" REBAR W/CAP LS BELL
- = FOUND 1/2" REBAR W/CAP LS 18092
- = 60' EASEMENT FOR INGRESS, EGRESS, AND UTILITIES, LYING 30' EACH SIDE OF C/L

ALL BEARINGS AND DISTANCES ARE WASHINGTON STATE PLANE COORDINATE GRID VALUES (SOUTH ZONE - NAD 83/91) BASED IN THE KITTITAS COUNTY GPS NETWORK, USCGS MONUMENTS AND USFS - WENATCHEE NATIONAL FOREST GPS MONUMENTS. THE COMBINED FACTOR USED FOR THIS PROJECT IS 0.9998681. TO OBTAIN ACTUAL GROUND DISTANCES, DIVIDE GRID DISTANCE BY 0.9998681.

BASIS OF BEARING: R-O-S FILED IN BK. 22, PG. 176 RECORDS OF KITTITAS COUNTY, WASHINGTON NW COR. TO THE S 1/16 COR WEST LINE

LINE CALL TABLE

COURSE	BEARING	DISTANCE
L-1	S 61°21'27"E	66.75'
L-2	S 50°26'37"E	115.68'
L-3	S 45°42'55"E	152.87'
L-4	S 53°05'44"E	309.58'
L-5	N 57°53'58"E	411.91'
L-6	N 57°53'57"E	225.10'
L-7	N 57°54'09"E	1173.05'
L-8	N 29°26'39"E	335.57'
L-9	N 29°26'39"E	264.02'
L-10	S 06°45'05"W	153.94'
L-11	S 05°29'10"E	43.85'
L-12	S 14°44'31"E	60.86'
L-13	S 19°13'22"W	146.44'
L-14	N 00°45'00"W	62.75'
L-15	N 08°23'12"E	185.31'
L-16	S 33°57'40"E	276.91'
L-17	OMMITTED	
L-18	S 45°51'33"E	100.45'
L-19	S 51°27'12"E	107.93'
L-20	S 66°51'57"E	244.15'
L-21	S 30°04'53"E	431.33'
L-22	S 27°47'53"E	202.96'
L-23	S 27°47'53"E	28.44'
L-24	S 34°47'03"E	94.97'
L-25	N 82°20'38"E	29.27'
L-26	N 82°20'38"E	162.94'
L-27	N 88°20'09"E	158.65'
L-28	S 87°55'45"E	242.80'
L-29	N 75°00'14"E	323.59'
L-30	N 87°08'15"E	232.07'
L-31	S 89°25'22"E	194.91'
L-32	S 34°47'03"E	99.93'
L-33	S 37°48'31"E	191.18'
L-34	S 37°48'31"E	174.60'
L-35	S 24°32'18"E	124.80'
L-36	S 24°32'18"E	316.78'
L-37	S 17°13'11"E	68.82'
L-38	S 29°26'39"W	568.97'
L-39	S 57°53'57"W	1265.28'
L-40	S 57°54'17"W	688.15'
L-41	N 53°05'44"W	305.71'
L-42	N 45°42'55"W	151.48'
L-43	N 50°26'37"W	123.89'
L-44	N 61°21'27"W	2.39'
L-45	S 08°23'12"W	69.03'

METHOD OF SURVEY

CONTROL USING TRIMBLE 4800 GPS RECEIVER, AND FIELD TRAVERSE USING TOPCON GTS-312 (00°00'03") TOTAL STATION. THIS SURVEY MEETS OR EXCEEDS THE ACCURACY STANDARDS AS SET FORTH IN WAC 332-130-090.

REFERENCE SURVEYS

- 1) SURVEY FILED IN VOL. 22, PG. 176 BY LS 18915
- 2) SURVEY FILED IN VOL. 27, PG. 138 BY LS 29269
- 3) SURVEY FILED IN VOL. 28, PG. 121 BY LS 29269

LINE CALL TABLE

COURSE	BEARING	DISTANCE
L-46	S 33°57'40"E	163.36'
L-47	N 73°55'14"E	165.40'
L-48	N 66°22'17"E	204.08'
L-49	N 83°00'26"E	122.07'
L-50	N 59°58'36"E	336.03'
L-51	S 05°17'41"E	179.20'
L-52	S 61°45'12"E	89.66'
L-53	S 10°26'55"W	235.81'
L-54	S 78°34'36"W	236.12'
L-55	S 32°44'33"W	132.51'
L-56	S 72°01'02"E	159.48'
L-57	S 83°30'37"E	213.34'
L-58	S 73°38'20"E	201.44'
L-59	S 75°48'07"E	134.77'
L-60	N 75°15'23"E	150.19'
L-61	N 75°15'23"E	161.41'
L-62	N 60°25'20"E	116.51'
L-63	N 68°48'48"E	142.10'
L-64	N 79°55'10"E	67.13'
L-65	N 88°03'31"E	8.80'
L-66	N 88°03'31"E	133.97'
L-67	S 78°23'19"E	96.45'
L-68	S 65°15'47"E	118.32'
L-69	S 42°35'57"E	108.36'

CURVE TABLE

CURVE	RADIUS	LENGTH	DELTA
C-1	403.66'	203.05'	28°49'17"
C-2	403.66'	280.75'	39°51'02"
C-3	458.68'	89.20'	11°08'34"
C-4	458.68'	136.79'	17°05'12"
C-5	174.08'	128.66'	42°20'51"
C-6	293.43'	22.46'	4°23'07"
C-7	163.86'	105.23'	36°47'36"
C-8	359.25'	183.88'	29°19'33"
C-9	507.32'	355.24'	40°07'12"
C-10	398.68'	57.87'	8°18'00"
C-11	398.68'	138.56'	19°54'47"
C-12	343.66'	411.89'	68°40'19"
C-13	30.00'	68.32'	130°29'14"
C-14	234.08'	173.01'	42°20'51"
C-15	212.45'	146.22'	39°26'06"
C-16	300.00'	356.72'	68°07'41"
C-17	293.43'	140.87'	27°30'27"
C-18	124.43'	122.62'	56°27'30"

SE COR. SEC. 7

4-23-02 FOUND 3-1/4" ALUM. MON. LS 18080 EXISTING R.P.'s:
 1) 13" FIR N37°W 23.00'
 NEW R.P.'s:
 2) 11" FIR S13°W 7.59'
 3) 6" FIR N18°E 14.35'



AUDITOR'S CERTIFICATE
 FILED FOR RECORD THIS 1st DAY OF June, 2004 AT 4:46 p.m. IN BOOK 30 OF SURVEYS AT PAGE 61
 AT THE REQUEST OF BLUHM & ASSOCIATES LAND SURVEYORS, INC.
 COUNTY AUDITOR: Sylvia Newkirk

SURVEYOR'S CERTIFICATE
 THIS MAP CORRECTLY REPRESENTS A SURVEY MADE BY ME OR UNDER MY DIRECTION IN CONFORMANCE WITH THE REQUIREMENTS OF THE SURVEY RECORDING ACT AT THE REQUEST OF CLE ELUM'S SAPPHIRE SKIES IN AUGUST, 2002.
 KEVIN BLUHM - LICENSE NO. 29269

ORIGINAL PARCEL DESCRIPTION
 LOTS A, B, E, F, G, AND H OF SURVEY FILED IN VOLUME 28, PAGE 121, UNDER AUDITOR'S FILE NO. 20021209004, RECORDS OF KITTITAS COUNTY, WASHINGTON.

BLUHM & ASSOCIATES LAND SURVEYORS, INC.
 1068 S. MARKET BLVD. CHEHALIS, WA 98532
 PHONE (360) 748-1551 FAX (360) 748-6282

DRAWN BY: K. HORTON	DATE: MAY 17, 2004	JOB # 01-530_V.dwg
CHECKED BY: KEVIN BLUHM	SCALE: 1" = 400'	COMP 4-ICAD
		SHEET 1 OF 1