WATER WELL REPORT

IF TRAINEE: Sponsor's License No.

Sponsor's Signature



Type of Work: State of Washington	Umique Ecology Well ID Tag No. BQH698	Kitti	tas-County CDS
☑ Construction	Site Well Name (if more than one well):	Nitt	ido Courty CDS
☐ Decommission	Water Right Permit/Certificate No.		
Proposed Use: Domestic Industrial Municipal			
☐ Dewatering ☐ Irrigation ☐ Test Well ☐ Other SHARED	Property Owner Name JOHN BARKER	- 1	
Construction Type: Method:	Well Street Address Mohart	voad	
☑ New well ☐ Alteration ☐ Drives ☐ Jetted ☐ Cable Tool	City C(E) County K	Hitag	
☐ Deepening ☐ Other ☐ Dug ☑ Air- ☐ Mud-Rotary	Tax Parcel No. 14362		
Dimensions: Diameter of boning 6 in., to 123 ft.			
Depth of completed well 121 ft.	Was a variance approved for this well? Yes	⊠ No	
Construction Details: Wall	If yes, what was the variance for?		
Casing Liner Diameter From To Thickness Steel PVC Welded Thread			
⊠ □ 6 in. 3 120 .250 in. ⊠ □ ⊠ □	Location (see instructions on page 2):		M or ⊠ EWM
	NW 1/4-1/4 of the SE 1/4; Section 3 Township 19		
	Latitude (Example: 47.12345) 47.165705	range 10	
	Longitude (Example: -120.12345) -120.950751		
Perforations:			
No. of perforations in. by in. Perforated from ft. to ft. below ground surface	Driller's Log/Construction or Decommission Procedure Formation: Describe by color, character, size of material and structure, and the kind and		
	nature of the material in each layer penetrated, with at les	and structure, and at one entry for a	the kind and sch change of
Screens: □ Yes ☑ No □ K-Packer	information. Use additional sheets if necessary.	-1020 0223 101 0	our counting of
Manufacturer's Name	Material	From	То
Type Model No ft. to ft.	TOPSOIL	0	3
Diameter Slot size in from ft. to ft.	CLAY	3	22
	CLAY/GRAVEL	22	50
Sand/Filter pack: Yes No Size of pack material in.	CLAY	50	60
Materials placed fromft. toft.	GRAVEL/SAND	60	100
Surface Seal: Yes No To what depth? 18 ft.	CLAY	100	106
Material used in seal BENTONITE Did any strata contain unusable water? □ Yes ☒ No	GRAVEL/SAND	106	123
Type of water? Depth of strata		100	123
Method of sealing strata off			
			
Pump: Manufacturer's Name Type:			
H.P Pump intake depth: ft. Designed flow rate: gpm			
Water Levels: Land-surface elevation above mean sea levelft.		_	
Stick-up of top of well casing ft. above ground surface			
Static water level <u>70</u> ft. below top of well easing Date <u>AUG 1 2024</u> Artesian pressure Ibs. per square inch Date			
Artesian water is controlled by(cap, valve, etc.)			
Well Tests: Was a pumping test performed? ⊠ No ☐ Yes ⇒ by whom?			
Yieldgpm with ft. drawdown after hrs.			
Yieldgpm withft. drawdown afterhrs.			
Yield gpm with 1. drawdown after hrs.			
Recovery data (time = zero when pump is turned off - water level measured from well			
top to water level)			
Time Water Level Time Water Level Time Water Level			
Date of pumping test			
Bailer test gpm with ft. drawdown after hrs.			
Air test 24 gpm with stem set at 103 ft. for 1 hrs. Date AUG 1			
Temperature of water ° F Was a chemical analysis made? □ Yes ❷ No			
	Start Date JULY 31 Completed Date		
WELL CONSTRUCTION CERTIFICATION: I constructed and/or accept resconstruction standards. Materials used and the information reported above are true	ponsibility for construction of this well, and its compli to my best knowledge and belief.	ance with all W	ashington well
☑ Driller ☐ Trainee ☐ PE - Print Name JEREMY BACH	Drilling Company RACH DRILLING CO		
Signature Signature	Drilling Company BACH DRILLING CO		
	Address 3340 WILSON CREEK ROAD		
License No. 2536	City, State, Zip ELLENSBURG WA 98926		

Notice of Intent No. WE56683

Contractor's

City, State, Zip ELLENSBURG

Registration No. MIKEBBD788RM

WA 98926